

SYNTHETIC PAPER

608

8 MIL C2S WHITE PET FILM - MATTE

DESCRIPTION

608 is an 8 mil, 2-side coated, synthetic paper made from high-grade polyester. Polyester films have superior dimensional stability, and the look and feel of premium paper. The result: great looking printed applications that hold their shape and color without extra laminates and coatings. **608** is waterproof and resistant to grease, chemicals and other liquids, characteristics that make the product suitable for both indoor and outdoor applications.

PHYSICAL CHARACTERISTICS

Caliper	8 mil
Basis Weight	230 g/m ²
Finish	Matte
Opacity	97%
Brightness	94%
Whiteness	NA
Smoothness	34
Lab Values	NA
Base material	PET Film
Structure	Coated
Melting Point (C°)	248

*All values are for reference only

FEATURES AND BENEFITS

- Dimensionally stable PET base film
- No grain direction
- Will not distort or stretch
- Superior registration
- Excellent print performance
- Excellent toner / ink adhesion
- Layflat
- Run consistently
- Waterproof, tear-proof and weather resistant
- Indoor and outdoor

PRINTER COMPATIBILITY

WF Toner - KIP / Oce / Xerox

Latex - HP / Mimaki

Toner Press - Canon / Konica Minolta / Xerox / Ricoh

UV - Fuji / Agfa / CET / HP / Oce / Mimaki / Vutek

*For additional information visit www.dietzgen.com

PROCESSING TIPS

- Preferred side out

PRINTING & FINISHING & PRINTING

- For all drilling and cutting, use sharp, clean blades
- Compatible with common folding and scoring equipment.
- Compatible with hot foil stamping and embossing
- Compatible with binding solutions including Wire-O® and Unicoil-Spiral®. Use round holes to avoid tearing

SHELF LIFE

2 years from ship date

STORAGE CONDITIONS

Temperature 50-85° F (10-30° C)

Relative Humidity 40-45%

OPTIMAL SERVICE ENVIRONMENT

Temperature 50-85° F (10-30° C)

Relative Humidity 40-45%