BOND PAPER

PRODUCT DATA SHEET

Rev 3 - Updated 8/18

74020LB BOND PAPER (HIGH BRITE)

DESCRIPTION

740 is 20LB high bright (96%) inkjet production bond paper. 740 provides good ink adhesion, print quality, line acuity and image clarity across multiple print technologies.

PHYSICAL CHARACTERISTICS

Caliper 4 mil Basis Weight 75 g/m2 20LB Bond Weight Brightness 96 Finish Matte Opacity 88% Whiteness 145 (CIE) Smoothness 170 Lab Values NA Base material Paper Structure Uncoated Acid Free / ECF PH

*All values are for reference only

FEATURES AND BENEFITS

- Good print performance
- Good toner / ink adhesion
- Good line acuity
- Good Image sharpness
- Good black density
- Smooth matte finish
- Acid free
- Elemental chlorine free (ECF)
- Meets ANSI Type I OCR dirt guidelines
- Meets ANSI Type III fluorescence guidelines
- Recyclable
- Can use pen / pencil to write on surface

PRINTER COMPATIBILITY



*For additional information visit www.dietzgen.com

*Does not guarantee optimal performance

PROCESSING TIPS

- Preferred side out

FINISHING & PRINTING

- Compatible with pressure sensitive, heat assist and thermal overlaminates.
- Allow sufficient time for inkjet prints to completely dry before rolling, laminating or cutting.
- Use a sharp blade to prevent ink and toner flaking on the edges
- Overlamination is not required. However, it can provide additional surface protection from dirt, abrasion and moisture.
- Can use pen / pencil to write on surface
- Compatible with common stapling and binding equipment

SHELF LIFE

2 years from ship date

STORAGE CONDITIONS

Temperature 50-85° F (10-30° C)

Relative Humidity 30-65%

OPTIMAL SERVICE ENVIRONMENT

Temperature 50-85° F (10-30° C)

Relative Humidity 30-65%

