ADHESIVE FILM

PRODUCT DATA SHEET Rev 3 - Updated 8/18

903 9 MIL POLYPROPYLENE FILM PSA - MATTE

PRINTER COMPATIBILITY



*For additional information visit www.dietzgen.com *Does not guarantee optimal performance

PROCESSING TIPS

- Preferred side out

FINISHING & PRINTING

- Compatible with pressure sensitive, heat assist and thermal overlaminates.
- Allow sufficient time for inkjet prints to completely dry before rolling, laminating or cutting.
- Use a sharp blade to prevent ink and toner flaking on the edges
- Overlamination is not required. However, it can provide additional surface protection from dirt, abrasion and moisture.

SHELF LIFE

2 years from ship date

STORAGE CONDITIONS

Temperature50-85° F (10-30° C)Relative Humidity30-65%

OPTIMAL SERVICE ENVIRONMENT

Temperature	50-85° F (10-30° C)
Relative Humidity	30-65%

DESCRIPTION

903 is a 9 mil, tear resistant, smooth, polypropylene banner with a low glare, satin finish, a water resistant, scratch resistant coating and a permanent pressure sensitive adhesive with removable liner. **903** provides excellent ink adhesion, print quality, black density, color pop and image clarity as well as exceptional strengh and durability for repeated handling products lay extremely flat, both on the printer and in final application. Short term outdoor.

PHYSICAL CHARACTERISTICS

Caliper	7 mil (without liner)
Basis Weight	NA
Brightness	NA
Opacity	90%
Finish	Matte
Whiteness	120
Smoothness	NA
Lab Values	NA
Base material	Polypropylene Film (PP)
Adhesive	Permanent Solvent Acrylic
Liner	Polyester
Structure	Coated
*All values are for r	eference only

FEATURES AND BENEFITS

- Tear Resistant Polypropylene Base
- Lay Flat
- Water Resistant
- Scratch Resistant
- Fast Drytime
- Excellent Print Performance
- Excellent Ink adhesion
- Excellent Line Acuity
- Excellent Image Sharpness
- ExcellentBlack Density
- Smooth Matte Finish

121 Kelsey Lane | Suite G | Tampa, Florida 33619 800-854-2341 | customerservice@dietzgen.com my.dietzgen.com | © Dietzgen Corporation

