



# KIP COLOR MEDIA GUIDE

## Bond Media

### Digital Vellum 20# - 80101

**Product Description** Our 100% cotton fiber vellum is transparentized using a proprietary non-Volatile Organic Compounds process and has a bright-white finish for strong visual contrast. Thru-put vellum meets Federal Specifications UU-P-561H for Type IV and is archive ready.

**Applications**

<p><b>Technical Applications:</b></p> <ul style="list-style-type: none"> <li>• Renderings</li> <li>• 3D Design</li> <li>• GIS Mapping</li> <li>• Geological Surveys</li> </ul>	<p><b>Business and Graphics Applications:</b></p> <ul style="list-style-type: none"> <li>• Education and Training</li> <li>• Temporary Sales Signage</li> </ul>
--	---

**Properties**

<p><b>Weight:</b> 20 lb. / 75 gsm</p>	<p><b>Opacity:</b> 60%</p> <p><b>Brightness:</b> 88</p> <p><b>Finish:</b> Matte</p>
---------------------------------------	---

**Width & Length** 24" x 500', 30" x 500', 36" x 500'

**Printer Conditions**

**Standard conditions apply:**  
**Temperature:** 59 to 80F / 15 to 27C  
**Relative Humidity:** 20 – 70% RH

**Storage Conditions** Store media in the same Temperature and Humidity as the printer. Media should be acclimated to the printer environment for 48 hours prior to use. Repack open rolls when not in use.

**Printer Settings**

Use the KIP Media Manager to select a compatible Media Name and corresponding Media Group based on the factory System Preset. This sets the correct Fuser Temperature, Transfer Voltages and Back up Data Settings for the specific media utilized at the correct Relative Humidity level.

**Media Name:** Vellum  
**Media Group:** Tracing (1)

To customize the corresponding Media Name, use the Media Manager COPY function to duplicate and name as required.

**Notes:**

- Heavy toner coverage can cause curling of the media at the edges