Presentation Bond - 8032

Product Description	A superior quality bond that is bright white for strong visual contrast. The heavy weight of the product eliminates curling on heavy coverage images and reduces show through. Provides durable output capable of handling very heavy toner coverage. Use for high-end proposals, presentations and short-term signage. Exceptionally smooth surface provides improved toner adhesion for optimal results.	
Applications	Technical Applications: Satellite Photo GIS Mapping CAD Cover Page Road Maps	Business and Graphics Applications: Temporary Signage Safety Poster Grocery Store Signage Variable Data Posters
	Display Graphics Applications:Digital PhotographyRetail Products	Banner Applications:Indoor Campaign SignageIndoor Party BannerPublic Events
Properties	Weight: • 32 lb. / 120 gsm • 83 lb. Text Stock • 46 lb. Cover Stock • 6 pt Stock	Opacity: 92% Brightness: 95 Finish: Matte
Width & Length	24" x 150', 24" x 400', 30" x 150', 30" x 400', 36" x 150', 36" x 400'	
Printer Conditions	Special conditions apply: Temperature: 59 to 80F / 15 to 27C Relative Humidity: 40 – 70% RH • Printer Conditions must be strictly adhered to for this media. Relative Humidity below 40% may cause print quality issues.	
Storage Conditions	Store media in the same Temperature and Humidity as the printer. Media should be acclimated to the printer environment for 48 hours prior to use. Repack open rolls when not in use.	
Printer Settings	Use the KIP Media Manager to select a compatible Media Name and corresponding Media Group based on the factory System Preset. This sets the correct Fuser Temperature, Transfer Voltages and Back up Data Settings for the specific media utilized at the correct Relative Humidity level.	
	Media Name: 32 lb. Presentation Bond Media Group: Paper Presentation (5)	
	To customize the corresponding Media Name, use the Media Manager COPY function to duplicate and name as required.	
Notes:	You may experience print quality issues based on heavy toner coverage, environmental conditions and system maintenance.	