



Product code: 4-GL3C-10167

## RI-JET 75 GLOSS WHITE AP940 PERMANENT GREYOUT WKPE90 AIRFLOW

### Uses

For use as promotional displays, point of purchase displays, trade show displays, and outdoor signage and banners. Grey primer enables high opacity, and airflow liner provides ease of application.

### Face Material

<b>Type</b>	Polymeric PVC
<b>Color and Finish</b>	White Gloss w/ Grey Primer
<b>Thickness</b>	3.0 mil ± 10%
<b>Durability* - unprocessed</b>	5 years <span style="float: right;">outdoor vertical exposure</span>

*\*The Durability data are given for unprocessed films only and based on zone 1 (Northern Europe & Northern USA) exposure conditions.*

### Adhesive

<b>Reference</b>	AP940
<b>Type</b>	Permanent
<b>Min. Appl. Temperature</b>	+50°F
<b>Service Temperature</b>	-40°F / +180°F
<b>Shear</b>	Very High
<b>Initial Adhesion</b>	2.5 lbs/in <span style="float: right;">FTM1 on steel</span>
<b>Final Adhesion</b>	3.5 lbs/in <span style="float: right;">FTM1 on steel</span>

### Liner

<b>Type</b>	Two-Side PE Coated Kraft w/ Airflow
<b>Colour and Finish</b>	White
<b>Weight</b>	90# ±10% <span style="float: right;">PP-032 - ISO 536</span>
<b>Thickness</b>	6.7 mil ±10% <span style="float: right;">ISO 534</span>

### Printing Methods

This film is printable on standard digital printers. Testing for suitability between media, printers and inks is always recommended prior to use.

### Shelf Life

12 months, applicable only to the material delivered by Ritrama which has not undergone further processing, under the under storage conditions as defined by FINAT section 2.5:

- Ideal storage conditions are at a temperature of 68 - 77 °F and 40 - 50 % HR.
- Store in a cool and dry place.
- Do not store close to a heat source or in direct sunlight.
- Keep the material in the original packaging until required for use.

Pay particular attention to the recommended shelf-life and ensure correct stock rotation.

### Substrate Preparation

All surfaces to which the material will be applied must be thoroughly cleaned with good quality cleaning solution. Ensure all traces of any contamination and cleaning agents are totally removed prior to application of the material. The compatibility of lacquers and paints should be tested by the user prior to the application.



### Application

Dry application only. Please refer to our Technical Bulletin ([www.ritrama.com](http://www.ritrama.com)) for specific technical details for the correct application and removal of the media.

### Disclaimer

*All Ritrama's products are subject to manufacturing controls in order to guarantee the good quality of the products. The statements, technical information, data, values and recommendations regarding Ritrama's products are based on research and tests we believe to be reliable, but do not constitute a guarantee or warranty of whatsoever nature.*

*Considering the multiple uses of Ritrama's products, the user is recommended to test the products prior to their use, so to determine and ascertain the suitability and performance of the product for its intended application and purpose.*

*The methods of conversion and application of Ritrama's self-adhesive materials are multiple and it is therefore essential that the users are aware of the particular method to be used, prior to commencing the production.*

*Printing: Testing for compatibility between product, printers and inks is always highly recommended before printing the product.*

*Application Systems and Conditions: it is recommended that the performance of the product be always tested in the actual applications conditions as substrate state (rough, smooth, flat or irregular shapes, moderate curves, with or without rivets); applicator technology (hand application or fully automated lines); specific stress on Ritrama material once applied (high and/or low temperature, mechanical stress, exposure to challenging environment conditions), et cetera.*

*As Ritrama's products are used in conditions beyond its control, such as those listed above as example, Ritrama does not assume any liability for inappropriate use of the products.*

*Ritrama reserves the right to modify at any time and without the need of a prior notice, at its sole and exclusive discretion, the products, their features and technical specifications.*

*All Ritrama's products are sold subject to Ritrama's general terms and conditions of sale listed in the following Ritrama's web page: <http://www.ritrama.com/en/sale-conditions/>*