

714

4 MIL / 90 g/m² / 24LB
C2S INKJET MATTE PAPER

DESCRIPTION

714 is 4 mil (24LB) inkjet matte coated paper featuring a smooth bright white surface. 714 proprietary instant dry coating produces good print quality, line acuity and image clarity across multiple inkjet print technologies without sacrificing print speed or color accuracy. 714 offers plug and play printing with standard onboard "coated paper" settings on most inkjet printers.

PHYSICAL CHARACTERISTICS

| | |
|---------------|---------------------|
| Caliper | 4 mil |
| Basis Weight | 90 g/m ² |
| Bond Weight | 24LB |
| Brightness | NA |
| Opacity | 96% |
| Finish | Matte |
| Whiteness | 111 |
| Smoothness | NA |
| Lab Values | NA |
| Base material | Paper |
| Structure | C2S Coated |

*All values are for reference only

FEATURES AND BENEFITS

- Bright white finish
- Instant dry
- Good ink adhesion
- Good line acuity
- Good black density
- Smooth matte finish
- Compatible with a variety of WF inkjet printers
- Compatible with thermal and PSA overlaminates
- No off setting
- Excellent post processing and finishing

PRINTER COMPATIBILITY



*For additional information visit www.dietzgen.com

*Does not guarantee optimal performance

PROCESSING TIPS

- Preferred side out

FINISHING & PRINTING

- Compatible with pressure sensitive, heat assist and thermal overlaminates.
- Allow sufficient time for prints to completely dry before rolling, laminating or cutting.
- Use a sharp blade to prevent ink flaking on the edges
- Overlamination is not required. However, it can provide additional surface protection from dirt, abrasion and moisture.
- Compatible with common stapling and binding equipment

SHELF LIFE

2 years from ship date

STORAGE CONDITIONS

| | |
|-------------------|---------------------|
| Temperature | 50-85° F (10-30° C) |
| Relative Humidity | 30-65% |

OPTIMAL SERVICE ENVIRONMENT

| | |
|-------------------|---------------------|
| Temperature | 50-85° F (10-30° C) |
| Relative Humidity | 30-65% |