ADHESIVE PAPER

PRODUCT DATA SHEET

Rev 3 - Updated 10/18

746PSA

6.5 MIL INKJET MATTE PAPER WITH PRESSURE SENSITIVE ADHESIVE

DESCRIPTION

746PSA is 6.5 mil Inkjet coated paper featuring a smooth bright white surface and a pressure sensitive adhesive. 746PSA proprietary instant dry coating produces good print quality, line acuity and image clarity across multiple print technologies without sacrificing print speed or color accuracy. 746PSA offers plug and play printing with standard onboard "coated paper" settings on most inkjet printers.

PHYSICAL CHARACTERISTICS

Caliper 6.5 mil (10 mil total)

Basis Weight 135 GSM **Bond Weight** 36LB 95 Brightness 98% Opacity Finish Matte Whiteness NA Smoothness NA Lab Values NA Base material Paper Structure Coated *All values are for reference only

FEATURES AND BENEFITS

- Instant dry
- Good ink adhesion
- Good line acuity
- Good black density
- Smooth matte finish
- Compatible with a variety of WF inkjet printers
- Compatible with thermal and PSA overlaminates
- No off setting
- Excellent post processing and finishing

PRINTER COMPATIBILITY



*For additional information visit www.dietzgen.com

PROCESSING TIPS

- Preferred side out

FINISHING & PRINTING

- Compatible with pressure sensitive, heat assist and thermal overlaminates.
- Allow sufficient time for inkjet prints to completely dry before rolling, laminating or cutting.
- Use a sharp blade to prevent ink and toner flaking on the edges
- Overlamination is not required. However, it can provide additional surface protection from dirt, abrasion and moisture.

SHELF LIFE

2 years from ship date

STORAGE CONDITIONS

Temperature 50-85° F (10-30° C)

Relative Humidity 30-65%

OPTIMAL SERVICE ENVIRONMENT

Temperature 50-85° F (10-30° C)

Relative Humidity 30-65%



^{*}Does not guarantee optimal performance