ADHESIVE PAPER

PRODUCT DATA SHEET

Rev 3 - Updated 8/18

75238LB PREMIUM MATTE INKJET PAPER - PSA

DESCRIPTION

752 is 5 mil (38 lb) premium inkjet coated matte paper with a smooth bright white surface and a permanent pressure sensitive adhesive with removable liner. **752** proprietary instant dry coating offers excellent ink and toner adhesion, print quality, line acuity and image clarity across multiple print technologies without sacrificing print speed or color accuracy.

PHYSICAL CHARACTERISTICS

Caliper 5 mil (10 mil total) 140 g/m² Basis Weight **Bond Weight** 38LB Brightness 104 Opacity 100% Finish Matte Whiteness NA Smoothness NA Lab Values NA Paper Base material

Adhesive Permanent Acrylic Liner Siliconized Paper

Structure Coated *All values are for reference only

FEATURES AND BENEFITS

- Instant Dry
- Excellent ink adhesion
- Excellent line acuity
- Excellent black density
- Smooth matte finish
- Compatible with a variety of WF inkjet printers
- Compatible with thermal and PSA overlaminates

PRINTER COMPATIBILITY



*For additional information visit www.dietzgen.com

PROCESSING TIPS

- Preferred side out

FINISHING & PRINTING

- Compatible with pressure sensitive, heat assist and thermal overlaminates.
- Allow sufficient time for inkjet prints to completely dry before rolling, laminating or cutting.
- Use a sharp blade to prevent ink and toner flaking on the edges
- Overlamination is not required. However, it can provide additional surface protection from dirt, abrasion and moisture.

SHELF LIFE

2 years from ship date

STORAGE CONDITIONS

Temperature 50-85° F (10-30° C)

Relative Humidity 30-65%

OPTIMAL SERVICE ENVIRONMENT

Temperature 50-85° F (10-30° C)

Relative Humidity 30-65%



^{*}Does not guarantee optimal performance