

# 906

## 11 MIL TYVEK® BANNER - MATTE

### DESCRIPTION

906 is a 11 mil outdoor durable, Tyvek® with a low glare, matte finish, a water resistant, scratch resistant coating for long lasting applications. The bright white, inkjet coating provides universal compatibility on most inkjet printers. It also provides water and fade resistance for long term outdoor use. 906 provides excellent ink adhesion, print quality, black density, color pop and image clarity as well as exceptional strength and durability for repeated handling Short term outdoor.

### PHYSICAL CHARACTERISTICS

Caliper	11 mil
Basis Weight	140 g/m <sup>2</sup>
Brightness	NA
Finish	Satin
Opacity	96%
Whiteness	120
Smoothness	NA
Lab Values	NA
Base material	Tyvek® or Polyethylene
Structure	Coated

\*All values are for reference only

### FEATURES AND BENEFITS

- Durable Tyvek® base material
- Water & fade resistant coating
- Excellent print performance
- Excellent ink adhesion
- Excellent black density and color pop
- Water / fade / scratch resistant coating
- Smooth matte finish
- Short term outdoor durable
- Grommeting and welding

### PRINTER COMPATIBILITY



\*For additional information visit [www.dietzgen.com](http://www.dietzgen.com)

\*Does not guarantee optimal performance

### PROCESSING TIPS

- Preferred side out

### FINISHING & PRINTING

- Allow sufficient time for prints to completely dry before rolling, laminating or cutting.
- Use a sharp blade to prevent ink and toner flaking on the edges
- Compatible with most brands of banner tape
- Compatible with most brands of grommets
- Grommets should be placed in multiple layers in the hemline (reinforced corners are also recommended)

### SHELF LIFE

2 years from ship date

### STORAGE CONDITIONS

Temperature	70° F (21° C)
Relative Humidity	50%
Temperature	50-85° F (10-30° C)
Relative Humidity	30-65%

### OPTIMAL SERVICE ENVIRONMENT

Temperature	50-85° F (10-30° C)
Relative Humidity	30-65%