

**950**  
5 MIL INSTANT DRY CLEAR FILM

**DESCRIPTION**

950 is a 5 mil dimensionally stable polyester film with a clear instant dry coating specifically designed for use in creating screen positives and negatives with dye or pigment aqueous inkjet printers.

**PHYSICAL CHARACTERISTICS**

Caliper	5 mil
Basis Weight	NA
Haze	>10%
Finish	Gloss
Base material	PET Film
Structure	Coated

\*All values are for reference only

**FEATURES AND BENEFITS**

- Dimensionally stable polyester film
- Accurate dot placement
- Minimal “yellowing”
- Instant dry
- UV “clear”
- High Dmax / Low Dmin

**PRINTER COMPATIBILITY**



\*For additional information visit [www.dietzgen.com](http://www.dietzgen.com)  
\*Does not guarantee optimal performance

**PROCESSING TIPS**

- Preferred side out

**FINISHING & PRINTING**

- Allow sufficient time for inkjet prints to completely dry before rolling, laminating or cutting.
- Use a sharp blade to prevent ink and toner flaking on the edges

**SHELF LIFE**

2 years from ship date

**STORAGE CONDITIONS**

Temperature	50-85° F (10-30° C)
Relative Humidity	30-65%

**OPTIMAL SERVICE ENVIRONMENT**

Temperature	50-85° F (10-30° C)
Relative Humidity	30-65%